



□ Installation Guide

JAC Marine JP100 Series Mount

Package Contents

Some of the items listed below are included only depending on the model selected at the time of order.

Qty	Part	Product Code	Applicable JP Models
1	Main plate	SA101-110-000	All
1	Pivot	SA300-000-000	All
1	Friction ring	SA300-000-001	All
1	30-inch tube	P100-030-000	All
1	Deluxe handle	AP100-108-000	All
3	Quick pins	GOU-250-137 NICL	All
3	Transducer cable clips	AP100-500-001	All
1	20-inch extension	AP100-100-020	JP100-XXX-050
2	30-inch extension	AP100-100-030	JP100-XXX-060
1	LiveScope / Active Target transducer mount	P100-210-000	JP100-000-XXX
1	LVS62 / Mega Live transducer mount	P100-210-325	JP100-001-XXX
1	LVS34 mount (front / bottom)	AP100-210-034	JP100-002-XXX
1	Pivot wrench (optional)	OU300	All

Installation Steps

1. Main Plate Installation

Attach the main plate and the required mount to the boat's edge. Refer to the installation guide specific to the mounting model you selected.

2. Mount Assembly

- Insert the pivot into the tube, with the smaller part facing downward.
- Slide the friction ring onto the pivot.
- Insert the handle on top of the pivot, on the side opposite the pivot outlet. It is held in place by a quick pin.
- Insert the 20 or 30 inch extension into the tube (opposite side from the handle).



- Then insert the transducer mount into the other end of the extension.

3. Height Adjustment

The transducer mount (or bottom of the support) should be aligned evenly or about 1" lower than the lowest part of the hull (usually the boat's V section).

4. Pivot Tightening

Once the height is set:

- Use a 1 ½ in wrench to tighten the main bolt. Do not overtighten.
- Once the part starts gripping the tube, use the handle to complete tightening.
- If the pivot rotates, use a second wrench (1 5/16 in) on the upper section to hold it steady. This step is rarely necessary.

5. Transducer Installation

Install the transducer on the purchased mount. For universal mounts, use the installation guide provided with the transducer.

6. Cable Management

Use the supplied clips and quick pins to securely attach the cable to the support.